

BAYBRITE ECO HIGH BAY





APPLICATIONS

- Ideal replacements for traditional HID fixtures
- Warehouse
- Storage Facilities
- Manufacturing
- Task Lighting
- Automotive Repair Garages
- 347-480v Ballast Available



FEATURES

- Same great features as standard BayBrite with Eco-Friendly body size
- Swing away reflector assembly for simple ballast access
- Fully enclosed fixture
- Convenient knockouts for mounting and electrical supply
- T5 or T8
- Wireguard & Door/Lens Options Available*
- Ballast Power Factor >98% — Low THD <10%
- T5 Fixture System Watts PSH**
- (6L-337; 8L-440; 10L-557; 12L-660)
- T8 Fixture System Watts ISH**
- (6L-223; 8L-292; 10L-369; 12L-438)



Series		Length		Width		# of Lamps		Type		Line Voltage		Reflector		Ballast Factor		Ballast Efficiency		Options
B	BayBrite Eco	4	4 Foot	14	4 Lamp	6	6 Lamp	T5	Fluorescent	1	Universal (120/277)	M	Miro 4	L	Low	T	Instant Start	0000
				14	6 Lamp	8	8 Lamp	T8	Fluorescent	2	347/480v			N	Normal	Q	Instant Start High Performance	
				20	8 Lamp								H	High	P	Program Start		

*Input wattage calculated using ballast manufacturer data in an open-air lamp application.

**Actual fixture wattage may vary based upon a variety of factors including: ballast factor; lamp wattage; input line voltage; ballast manufacturer; and/or environmental temperature.