

APPLICATIONS

- Food Processing Facilities
- Refrigerated Storage
- Parking Garages
- Breweries and Bottling Facilities
- Livestock Facilities
- Gymnasiums

CERTIFICATIONS

- Tested/Certified by NSF International
- UL Wet Location
- NEMA 4X
- IP66/IP67
- ROHS

FEATURES

- Designed for tough environments
- Weatherproof enclosures
- T5 or T8
- Easy to clean and service
- Variety of lamp combinations (3,4,5,6)
- Impact resistant lenses
- Stainless steel hardware
- Simple mounting system—no holes to drill!



Mounting Options



Cable Mount

Series		Length		# of Lamps		Type		Line Voltage		Reflector		Ballast Factor		Ballast Efficiency		Options	
VH	Vaportite High Bay	4	4 Foot	3	3 Lamp	T5	Fluorescent	1	Universal (120/277)	MR	Miro 4	L	Low	T	Instant Start	0000	
				4	4 Lamp	T8	Fluorescent	2		347/480v	BC	Ballast Cover	N	Normal	Q		Instant Start High Performance
				5	5 Lamp								H	High	P		Program Start
				6	6 Lamp												

*Input wattage calculated using ballast manufacturer data in an open-air lamp application.

*Actual fixture wattage may vary based upon a variety of factors including: ballast factor; lamp wattage; input line voltage; ballast manufacturer; and/or environmental temperature.